

VERNO LEVELITE - FUNCTION OVERVIEW

| | VERNO LEVELITE | VERNO LEVELITE XL | VERNO LEVELITE XP | VERNO LEVELITE IHP |
|--|----------------|-------------------|-------------------|--------------------|
| Light emitting module | | | | |
| Wired module | ■ | ■ | ■ | |
| Inductively coupled module | | | | ■ |
| Control unit | | | | |
| VERNO CONTROL MINI / DUO | ■ | ■ | | |
| VERNO CONTROL IHP | | | | ■ |
| VERNO CONTROL XP | | | ■ | |
| Control unit suitable for mounting on top hat rails | ■ | ■ | ■ | |
| Power supply and control unit executed separately | ■ | ■ | ■ | |
| Functions | | | | |
| Continuous illumination | ■ | ■ | ■ | ■ |
| Flashing with external clock | ■ | ■ | ■ | ■ |
| Flashing with internal clock | | | ■ | ■ |
| Reverse side of module can be switched off | ■ | | ■ | ■ |
| Running light | ■ | | ■ | |
| Gradually increasing illumination | | | ■ | |
| Gradually decreasing illumination | | | ■ | |
| Day / Night dimming | ■ | ■ | ■ | ■ |
| Brightness adjustment | ■ | ■ | ■ | ■ |
| Module feedback | | | ■ | |
| System power supply | | | | |
| 2,000 m length power supply | | | | ■ |
| Functional extra-low voltage < 60 V DC | ■ | ■ | ■ | |
| EMC tested | ■ | ■ | ■ | ■ |
| Potential free contacts to control the light-emitting modules | ■ | ■ | ■ | |
| Electronically compensated line losses | | | ■ | |
| Without resonant circuit adjustment (e.g. via compensator devices) | ■ | ■ | ■ | |
| Connection to tunnel technology | | | | |
| Feedback from the control unit via potential-free contacts | ■ | ■ | ■ | ■ |
| LAN connection available at control unit | | | ■ | |
| Control through RS232 | | | ■ | |

VERNO LEVELITE - FUNCTION OVERVIEW

| | VERNO LEVELITE | VERNO LEVELITE XL | VERNO LEVELITE XP | VERNO LEVELITE IHP |
|--|----------------|-------------------|-------------------|--------------------|
| Data communication | | | | |
| Assignment of unique adress for each module | | | ■ | |
| Feedback from the entire line | ■ | ■ | ■ | ■ |
| Feedback from individual modules | | | ■ | |
| Status feedback from the control unit to the upper-level control | | | ■ | |
| Assignment of fixed module addresses | ■ | | ■ | |
| Assignment of flexible module addresses | | | ■ | ■ |
| Cyclic module query | | | ■ | |
| Faciliated error search, power supply with DC | ■ | ■ | ■ | |
| Installation | | | | |
| 2 x 2.5 mm ² special braid for cabling | ■ | ■ | ■ | |
| 2 x 6 mm ² special braid for cabling | | | | ■ |
| T-Connector HD, IP 68 | ■ | ■ | ■ | |
| Inductive signal and power transmission | | | | ■ |